

Boom & Scissor Lifts (EWP)

ARTICULATING Z-BOOMS										
MODEL	WORKING HEIGHT		WIDTH		HORIZONTAL REACH		UP & OVER CLEARANCE		LIFT CAPACITY	
	Metric	US	Metric	US	Metric	US			Metric	US
NARROW ARTICULATING Z-BOOMS										
Z - 30/20N RJ	10.89 m	35 ft 2 In	1.19 m	3 ft 11 In	6.25 m	20 ft 6 In	3.86 m	12 FT 8 In	227 kg	500 lbs
Z - 34/22N	12.52 m	40 ft 6 In	1.47 m	4 ft 10 In	6.78 m	22 ft 3 In	4.62 m	15 ft 2 In	227 kg	500 lbs
Z - 40/23N RJ	14.32 m	46 ft 5 In	1.50 m	4 ft 11 In	6.91 m	22 ft 8 In	6.48 m	21 ft 3 In	227 kg	500 lbs
DC ARTICULATING Z -BOOMS										
Z - 45/25J DC	15.52 m	51 ft 8 In	1.79 m	5 ft 10.3 In	7.65 m	25 ft 1 In	6.73 m	22 ft 1 In	227 kg	500 lbs
ENGINE-POWERED ARTICULATING Z-BOOMS										
Z-34/22 IC	12.62 m	40 ft 10 In	1.85 m	6 ft 1 In	6.78 m	22 ft 3 In	4.57 m	15 ft	227 kg	500 lbs
Z-45/25J RT	10.07m	52 ft 2 In	2.29 m	7 ft 6 In	7.65 m	25 ft 1 In	7.16 m	23 ft 6 In	227 kg	500 lbs
Z-51/30J RT	17.62m	57 ft 3 In	2.29 m	7 ft 6 In	9.25 m	30 ft 4 In	7.49 m	24 ft 6 In	227 kg	500lbs
Z-60/34	20.39 m	66 ft 4 In	2.46 m	8 ft 1 In	11.05 m	36 ft 3 In	8.23 m	27 ft	227 kg	500lbs
Z-80/60	25.77 m	84 ft	2.49 m	8 ft 1 In	18.29 m	60 ft	8.8m	29 ft	227 kg	500 lbs
Z-135/70	43.15 m	14 ft	2.46 m	8 ft 1 In	21.26 m	69 ft 9 In	23.01 m	75 ft 6 In	272 kg	600 lbs

TELESCOPIC S-BOOMS								
MODEL	WORKING HEIGHT		WIDTH		HORIZONTAL REACH		LIFT CAPACITY	
	Metric	US	Metric	US	Metric	US	Metric	US
STICK TELESCOPIC S-BOOMS								
S-45	15.72 m	5 ft	2.30 m	7 ft 6 In	11.18 m	96 ft 8 In	227 kg	500 lbs
S - 65	21.80 m	71 ft	2.49 m	8 ft 2 In	17.10 m	56 ft 2 In	227 kg	500 lbs
S - 65 TRAX	21.86 m	71 ft 2 In	2.59 m	8 ft 6 In	17.10 m	56 ft 2 In	227 kg	500 lbs
S - 86	27.70 m	91 ft	2.50 m	8 ft 2 In	23.30 m	76 ft 6 In	227 kg	500 lbs
SUPER TELESCOPIC S-BOOMS								
S - 125	40.a5 m	13 ft 2 In	2.49 m	8 ft 2 In	24.38 m	80 ft	227 kg	500 lbs

SELF-PROPELLED SCISSORS										
MODEL	WORKING HEIGHT		WIDTH		TURNING RADIUS OUTSIDE		LIFT CAPACITY		GRADEABILITY	
	Metric	US	Metric	US	Metric	US	Metric	US		
ELECTRIC SCISSOR LIFTS										
GS - 1532	6.57 m	21 ft	0.81 m	2 ft 8 In	1.55 m	5 ft 1 In	272 kg	600 lbs	30%	
GS - 1932	7.79 m	25 ft	0.81 m	2 ft 8 In	1.55 m	5 ft 1 In	227 kg	500 lbs	25%	
GS - 2032	8.10 m	26 ft	0.81 m	2 ft 8 In	2.13 m	7 ft	363 kg	800 lbs	30%	
GS - 2632	9.92 m	32 ft	0.81 m	2 ft 8 In	2.13 m	7 ft	227 kg	500 lbs	25%	
GS - 3232	11.75 m	38 ft	0.81 m	2 ft 8 In	2.13 m	7 ft	227 kg	500 lbs	25%	
GS - 2046	8.10 m	26 ft	1.17 m	3 ft 10 In	2.29 m	7 ft 6 In	544 kg	1,200 lbs	30%	
GS - 2646	9.92 m	32 ft	1.17 m	3 ft 10 In	2.29 m	7 ft 6 In	454 kg	1,000 lbs	30%	
GS - 3246	11.75 m	38 ft	1.17 m	3 ft 10 In	2.29 m	7 ft 6 In	318 kg	700 lbs	26%	
ROUGH TERRAIN SCISSOR LIFTS										
GS - 2660 RT	9.92 m	32 ft	1.75 m	5 ft 9 In	4.60 m	15 ft	680 kg	1,500 lbs	35%	
GS - 3360 RT	11.96 m	39 ft	1.75 m	5 ft 9 In	4.60 m	15 ft	454 kg	1,000 lbs	30%	
GS - 4060 RT	14.19 m	46 ft	1.75 m	5 ft 9 In	4.60 m	15 ft	363 kg	800 lbs	30%	
GS - 3384 RT	12.06 m	39 ft	2.13 m	7 ft	5.94 m	19 ft 6 In	1,134 kg	2,500 lbs	50%	
GS - 4300 RT	15.11 m	49 ft	2.29 m	7 ft 6 In	5.33 m	17 ft 6 In	680 kg	1,500 lbs	50%	
GS - 5300 RT	18.15 m	59 ft	2.29 m	7 ft 6 In	5.33 m	17 ft 6 In	680 kg	1,500 lbs	40%	